

# AeroMesh™

## 3.4 oz.

### BRIEF DESCRIPTION

- 100% polyester soft textured mesh with semi-gloss finish
- Excellent ink penetration with Dye-Direct printing
- Great for short-term fence graphics

### FEATURES



PVC-FREE



PHthalate FREE

### INK PRINTABILITY



DYE  
DIRECT



DYE  
PAPER

### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
<b>Weight</b>	DIN EN ISO 2286-2, ASTM D751	115 g./sq. m.	3.4 oz./sq. yds.
<b>Base Fabric</b>	DIN 60001, ASTM D7641	100% POLYESTER	
<b>Weave Method</b>	N/A	WARP-KNITTED	
<b>Air Permeability</b>	N/A	4010 L/M <sup>2</sup> /s	
<b>Shrinkage</b>	ISO 9866-2-1991	≤ 2%	
<b>Flame Resistance</b>	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
<b>Recommended Fixation Temperature</b>	N/A	190° C, 30 s	
<b>Unit Width</b>	DIN EN ISO 3759, ASTM D751-2006	177.8, 233.68, 320.04 cm.	70, 92,126 in.
<b>Unit Length</b>	DIN EN ISO 3759, ASTM D751-2006	100, 201 m.	110, 220 yds.

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data are the average of test results and should not be used for the purpose of lawsuits or warranty.



info@kedermacroprint.com  
602-892-1000  
kedermacroprint.com

A division of **keder**  
SOLUTIONS