

Nexus Blackback™ 7.9 oz.

BRIEF DESCRIPTION

- 100% warp-knitted polyester fabric with white surface and black resin coated backing, offers full opacity
- Slight stretch features makes it perfect as frame and pop-up materials

FEATURES



PVC-FREE



PHTHALATE FREE



FULL OPACITY



PROPER STRETCH

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Weight	DIN EN ISO 2286-2, ASTM D751	270 g./sq. m.	7.9 oz./sq. yds.
Base Fabric	DIN 60001, ASTM D7641	100% POLYESTER	
Weave Method	N/A	WARP-KNITTED	
Shrinkage	210° C, 30 s	≤ 3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1 EN13501-1	DIN 4102-1-B1, NFPA 701 Test1 EN13501-1	
Recommended Fixation Temperature	N/A	190° C - 210° C, 1-2 min.	
Yellowing Temperature	SUPRKC REX-C400, 30 s	≥ 210° C	
Unit Width	DIN EN ISO 3759, ASTM D751-2006	MAX 320 cm.	126, 196 in.
Unit Length	DIN EN ISO 3759, ASTM D751-2006	100 m.	110 yds.

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data are the average of test results and should not be used for the purpose of lawsuits or warranty.



info@kedermacroprint.com
(602) 892-1000
kedermacroprint.com

A division of **keder**
SOLUTIONS