

PVC Mesh

8 oz.

BRIEF DESCRIPTION

- 60/40 Mesh
- Soft and clean surface
- The most commonly used PVC mesh solution on the market
- Widely used for fence graphics, barricade covers, scaffolding, large format advertisements and large banners that require air flow-through

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Weight	DIN EN ISO 2286-2	270 g./M ²	8 oz./sq. yds.
Base Fabric	DIN 60001	POLYESTER	
Yarn Dtex	DIN EN ISO 2060	1100 X 1100 DTEX	1000 X 1000 DENIER
Tensile Strength	DIN EN ISO 1421	1750 X 1400 N/5 cm.	195.7 X 156 lbs./in.
Tear Strength	DIN 53363	750 x 550 N	168 x 123 lbs./in.
Flame Resistance	DIN 4102	NFPA 701, B1, M2	
Unit Width	N/A	MAX 500 cm.	126, 196 in.
Unit Length	N/A	50, 100 m.	55, 110 yds.

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data are the average of test results and should not be used for the purpose of lawsuits or warranty.



info@kedermacroprint.com
(602) 892-1000
kedermacroprint.com

A division of **keder**
SOLUTIONS