

AeroMesh[®]

3.4 oz.

BRIEF DESCRIPTION

- 100% polyester soft textured mesh with semi-gloss finish
- Excellent ink penetration with Dye-Direct printing
- Great for short-term fence graphics

FEATURES



PVC-FREE



PHthalate FREE

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Weight	DIN EN ISO 2286-2, ASTM D751	115 g./sq. m.	3.4 oz./sq. yds.
Base Fabric	DIN 60001, ASTM D7641	100% POLYESTER	
Weave Method	N/A	WARP-KNITTED	
Air Permeability	N/A	4010 L/M ² /s	
Shrinkage	ISO 9866-2-1991	≤ 2%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommended Fixation Temperature	N/A	190° C, 30 s	
Unit Width	DIN EN ISO 3759, ASTM D751-2006	177.8, 233.68, 320.04 cm.	70, 92, 126 in.
Unit Length	DIN EN ISO 3759, ASTM D751-2006	100, 201 m.	110, 220 yds.

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data are the average of test results and should not be used for the purpose of lawsuits or warranty.



info@kedermacroprint.com
602-892-1000
kedermacroprint.com

A division of **keder**[®]
SOLUTIONS