

Quantum Greyback®

9.7 oz.

BRIEF DESCRIPTION

- 100% warp-knitted polyester fabric with enhanced white surface
- Uncoated greyback offers crease-free performance when folded
- Soft hand touch, slight stretch & good opacity, a unique solution
- A great option for backdrops where you don't want to see the frame

FEATURES



PVC-FREE



PHthalate FREE



PROPER STRETCH



GOOD OPACITY



WRINKLE-RESISTANT

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Weight	DIN EN ISO 2286-2, ASTM D751	330 g./sq. m.	9.7 oz./sq. yds.
Base Fabric	DIN 60001, ASTM D7641	100% POLYESTER	
Weave Method	N/A	WARP-KNITTED	
Shrinkage	ISO 9866-2-1991	≤ 2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	99%	
Elasticity	LENGTH * WIDTH = 200 * 50 mm. SPEED = 100 mm./min. TENSION = 20 N	WARP: 10% WEFT: 5%	
Flame Resistance	DIN 4102-1-B1, NFPA 701, EN13501-1	DIN 4102-1-B1, NFPA 701, EN13501-1	
Recommended Fixation Temperature	N/A	190° C, 30 s	
Unit Width	DIN EN ISO 3759, ASTM D751-2006	MAX 320 cm.	126, 196 in.
Unit Length	DIN EN ISO 3759, ASTM D751-2006	50 m.	55 yds.

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data are the average of test results and should not be used for the purpose of lawsuits or warranty.



info@kedermacroprint.com
(602) 892-1000
kedermacroprint.com

A division of **keder**
SOLUTIONS