keder MACROPRINT®
Your Vision. Our Supply.

TECHNICAL DATA SHEET

KederTac™ 84-RO Blackback Removable Decal Material

INK COMPATIBILITY

SOL | ECO SOL | UV | LATEX

BRIEF DESCRIPTION

Print, Cut and Go with this NEW revolutionary removable decal material. 100% opaque with a blackback layer and zero light transmission, clean removability, air egress adhesive for easier installation, and faster production with NO LAMINATION required.

- 8.4 mil. Double Layer Construction
- Clean Removal for up to 6 months (w/o heat)
- 100% Opaque – Zero Light Transmission
- Matte White Print Face + Black Blockout Layer
- Clear Air-Egress Adhesive for Fast and Bubble-Free Installation
- 60 in. x 50 yd. Rolls (750 sq/ft per roll)

NOT Intended For:

- Complex Curves
- Rivets
- Low Energy Surfaces
- Permanent Graphics
- Wet Applications

KEY SPECS

Material Detail	Calendered PVC Vinyl, Matte White/Black
Thickness	Film + Adhesive +/- 8.4 mil.
Adhesive Type	Clear, Low-tack Removable, Air-Egress
Film Opacity	>99%
Application Temperature Range	>50° F
Service Temperature Range	-20° F to 180° F
Peel Adhesion (Stainless Steel)	15 min., 0.7 (lbs./in.) 24 hrs., 1.0 (lbs./in.)
Removability	Cleanly up to 6 Months, Max. 1 Year
Indoor Durability (Unprinted)	3 Years
Outdoor Durability (Unprinted)	Dependent on Environmental and Surface Conditions

NOTE: It is normal that the weight of most products will have an average fluctuatuion of 5%. All above information shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data are the average of test results and should not be used for the purpose of lawsuits or warranty.

info@kedermacroprint.com
(602) 892-1000
kedermacroprint.com
A division of keder SOLUTIONS